Sr. No.	Questions	Α	В	С	D	Correct
1	provides a way to differentiate between SCSI devices sharing a single SCSI ID.	LAN	VLAN	LUN	WAN	С
	WAN design involves the aggregation of many branch	hub-and-				
2	sites into one headend site in a fashion.	spoke	mesh	bus	ring	Α
		General	Generic	General	Generic	
		Routing	Routing	Routing	Routing	
		Encapsul	Extensi	Extensi	Encapsul	
3	GRE stands for	ation	on	on	ation	D
			Route	Routing		
		Route	Informa	Informa	Routing	
	The is the memory structure that contains	Internet	tion	tion	Internet	
4	classic routing data.	Base	Base	Base	Base	С
	decouples packet forwarding from the					
5	information in the IP header.	GRE	RIB	PPTP	MPLS	D
	An router forwards packets based on fixed-					
	length labels instead of matching on a variable-length IP					
6	address prefix.	GRE	RIB	MPLS	PPTP	С
	The hardware that contains the host controller and the					
7	root hub is called the	HCD	NAT	UHCI	EHCI	Α
8	A server is another term for a virtual machine.	host	guest	remote	partition	В
	partitioning is a software-based technology					
	in which a single application instance provides multiple,		Softwar		Applicati	
9	isolated instances of a service	Resource	е	Service	on	С
	The isolation of each soft partition and the management					
	of the shared resources of the computer are completely					
10	handled by a special software layer called a	VMM	VM	SoftV	HardV	Α
	is a concept in which an environment imitates	Emulatio	Simulati	Virtualiz	Hypervis	
11	another environment.	n	on	ation	or	В
			Networ			
			k	Neural		
		Next	Attache	Attache	Network	
		Attached	d	d	Attached	
12	NAS stands for	Storage	System	System	Storage	D
	The engine used to run hardware virtualization is usually		hypervi			
13	referred to as a	VMM	sor	SoftV	HardV	В
	is the last step focuses on the update of the					
	tools you use to maintain complete virtualization		Virtualiz	Architec	Manage	
14	scenarios in your new dynamic datacentre.	Discovery	ation	ture	ment	D
	Virtualization is done with a hardware					
	emulation tool and processor-based virtualization					
	support that allows you to run unmodified guest kernels					
15	that are not —aware they are being virtualized.	Full	Para	Semi	Half	Α
	Virtualization is focused on partitioning a					
	physical instance of an operating system into a virtual			Networ		
16	instance or virtual machine.	Desktop	Storage	k	Server	D
	Group of resistors placed on the end of a SCSI bus that					
	prevents deflection of SCSI signals are called	Terminat	Reflecto	Amplifie		
17		or	r	r	HBA	Α

	acts as an interface between the SCSI bus and				Terminat	
18	a host computer.	LUN	SCSI	НВА	or	С
			High	Low		
		Single-	voltage	voltage		
	With interface, all electronic signals travel	ended	differen	differen	Host Bus	
19	over a single wire and ground connection.	SCSI	tial	tial	Adapter	Α
	Fiber-optic cable allows for a maximum					
	distance of 10 kilometers and offers a bandwidth of	Multimo	Single-	Intracab	Intercabi	
20	4Gbps with plans for expansion to 10Gbps.	de	mode_	inet	net	В